




Nexus One Flash Replacement

This guide is for installing the flash on the Nexus One.

Written By: Niklas Johnson



INTRODUCTION

installing the flash

TOOLS:

- [iFixit Opening Tools](#) (1)
 - [Spudger](#) (1)
 - [Phillips #00 Screwdriver](#) (1)
 - [T5 Torx Screwdriver](#) (1)
-

Step 1 — Rear Cover



- Using two fingers, push up on the rear cover.

Step 2



- The rear cover slides up and off.

Step 3 — Battery



- Using the plastic opening tools, pry the left bottom corner of the battery up.

Step 4



- Pull the battery up and out.

Step 5 — Battery Housing



- Remove the two Torx T5 screws.
- Remove the one Philips #00 screw.

Step 6



- Using the plastic opening tool, pry up the battery housing upwards.
- Push pry tool down, undoing the plastic tab.

Step 7



- Pry the upper left tab open on the battery housing.


Step 8



- Pry the top tab of the battery housing.




- ## Step 10



- Page 7 of 8

Step 11 — Flash



- Insert the spudger under the bottom of the flash board
- Twist the spudger to lift and release the flash board.

To reassemble your device, follow these instructions in reverse order.

This document was last generated on 2017-06-26 05:22:26 AM.